



**10mm Aluminum Alloy Bezel
Silver (stainless steel color)**



stainless steel color Bezel



Rear View



I/O port

12.1" TFT Panel PC with low power 800Mhz CPU/Touch / LAN / 4 x COM / 2 x USB / Audio / CDROM

General specifications

Display

12.1" color TFT flat panel

Display Type

800 x 600 TFT LCD panel

Luminance

150~200 cd/m2 brightness luminance

CPU

P-III equivalent Low power 800Mhz
CPU L1 & L2 cache built on CPU

System Chipset

Twister-T , VIA VT8606 , 82C686B

Front Bezel

Thick 10mm Aluminum-alloy hairline
anodizing treatment front bezel

Housing & Wall-mounting

Rugged 1.2mm thick steel metal with
white painting VESA-75 and VESA-100
compliant

Surface Treatment of Front Panel

Super high-end hairline anodizing
treatment, color

Standard Colors

Stainless Steel silver color

Front Panel Protection

Meet NEMA 4, 12 and IP65, 56 water
resistant EIA standard

System Memory (Optional)

PC133 SDRAM support up to 512MB

CD-ROM

One slim size CD-ROM, 24x speed

HDD (optional)

20 - 30GB slim size HDD

Disk On Module (optional)

Support DOM up to 512MB

DiskOnChip(optional)

Support M-System's DOC up to 288MB

Serial ports

4x COMs (3 x RS232 port ,1 xRS232/422/485
port)

USB

2 x USB ports and IrDA pin header on board

Parallel Port

LPT port for Printer connection.

Keyboard and Mouse

One PS/2 KB/Mouse port

Audio

Microphone, Speaker, Line-in

Network Interface Controller Chipset

Realtek 8139C ,support 10/100 Mbp,
auto-negotiation ,auto-switch LAN

Vibration: 5-17Hz, 0.1"double amplitude

displacement 17-500Hz, 1.5G acceleration
peak to peak

Shock : 10G acceleration peak to peak
(11ms)

VGA - Display Controller Chipset

Trident chipset support 24bit LCD TFT
LCD/2-channel LVDS, TFT, DSTN
LCD/CRT with 8MB share Video
memory, 3D/2D support

DVD MPEG-2

support DVD video playback

Touch Panel (Optional)

Long-life 6-wire resistive Touch screen

PCI expansion slot

1 x PCI slots for expansion purpose

Environmental and Power

Requirements

Internal UL/CE safety approved
power supply

Dimension (WxHxD)

Please call our sales

Operating Temperature :

0 to 55°C (32 to 131°F)

Ordering information