

PPC-157T 15" Panel PC with Low Power 800Mhz CPU with VGA / LAN / Audio / 4xCOM / 2xUSB




Ultra thick solid Aluminum Alloy
IP-65, NEMA 4, VESA-75, 100



Cable-Less Design for best
Vibration & Shock resistant



Tapped screw holes,
VESA 75 and 100,



fill water into panel until full




USB, LAN, Audio, 4xCOM,
Printer, KB, Mouse



Screw mount



Quick wall-mounted Kit



100% Water-Resistant Test on
front panel for 7 days

15.1" TFT Panel PC with Touch / LAN / 4 x COM / 2 x USB / Audio / CD-ROM

LCD Display

15" color TFT LCD, 1024 x 768 high resolution
250 cd/m² high brightness

CPU - Low Power 800Mhz

P-III equivalent **Low power** 800Mhz CPU
soldered on board, (Low Power **1Ghz** is optional)

System Chipset

VIA VT8601 Northbridge and VIA686B

System Memory : (Optional)

Support up to 512MB SDRAM memory

Touch Panel :

Long life 5-Wire Resistive touch screen optional

Front Bezel

Thick 10mm solid Aluminum-alloy, with highest level surface treatment

Housing & Wall-mounting

Rugged 1.2mm thick steel metal sheet with white painting
VESA -75 and VESA-100 compliant

Water-Resistant on Front Panel

Meet IP-56, 65, NEMA 4, 12 water resistant

Surface Treatment of Front Panel

Super high-end polish, sand-blast, hairline anodizing treatment. Standard color is Stainless Steel silver Color or Black

CD-ROM : One CD-ROM, 24x speed

HDD : (Optional) 20 or 30GB HDD

10, 20, or 30GB slim size HDD is (Optional)

Disk On Module - (Optional)

Support DOM up to 512MB (optional)

Serial ports : 4 x COM ports

(3 x RS232 ports and 1 x RS232/422/485)

1 x COM was assigned for touch screen

USB port : 2 x USB ports

Quick wall-mount Kit – special design

Nagasaki Special design quick wall-mount kit

Parallel Port : LPT port for Printer connection.

Keyboard and Mouse : One PS/2 KB Mouse

Audio – built in high quality speakers

Built in high quality speakers, Microphone jack, Line-in jack

Ethernet Network Controller

Realtek 8139C, support 10/100 Mbps, auto-negotiation, auto-switch LAN

VGA - Display Controller Chipset

Trident chipset support AGP 4X LCD/CRT with 8MB share Video memory, 3D/2D support
DVD MPEG-2 : support DVD video playback

Vibration-Resistant Design

Excellent cable-less design for vibration and shock resistant ability,
5 - 17 Hz, 0.1" double amplitude displacement,

17-500 Hz, 1.5G acceleration peak to peak

Shock-Resistant Design

10G acceleration peak to peak (11 msec. duration)

Power Supply : AC-DC or DC-DC optional

External power supply UL/CE safety approved

DC-DC Power supply is optional

Dimension (WxHxD)

Please call our sales

Operating Temperature :

0 to 55°C (32 to 131°F)

Ordering information :

PPC-157 : without Touch

PPC-157T : with Touch screen